

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat T770

⊖ Engine

| | |
|-----------------------------|-------------------------------------|
| Emissions Tier (EPA) | Tier 3 |
| Engine Cooling | Liquid |
| Engine Fuel | Diesel |
| Horsepower | 67,6 kW |
| Turbocharged Engine | <input checked="" type="checkbox"/> |

⊖ Performance

| | |
|--|-----------|
| Rated Operating Capacity (SAE) | 1611 kg |
| Operating Capacity (50% of Tip) | 2115 kg |
| Tipping Load | 4309 kg |
| Operating Weight | 4663 kg |
| Travel Speed | 10.6 km/h |
| Travel Speed (2-speed option) | 17.2 km/h |
| Ground Pressure (Rubber) | 0.29 bar |

⊖ Capacities

| | |
|------------------|---------|
| Fuel Tank | 166.4 l |
|------------------|---------|

⊖ Hydraulic System

| | |
|---------------------------------------|-------------|
| System Relief @ Quick Couplers | 241,5 bar |
| Auxiliary Std Flow | 87,1 l/min |
| Auxiliary High Flow | 138,2 l/min |

⊖ Dimansion

| | |
|------------------------------------|---------|
| Length | 3597 mm |
| Length without Attachment | 2903 mm |
| Length with Standard Bucket | 3597 mm |
| Width | 1981 mm |
| Width (with bucket) | 2032 mm |
| Height | 2065 mm |
| Height with Operator Cab | 2065 mm |
| Height to Bucket Hinge Pin | 3353 mm |
| Reach @ Maximum Height | 853 mm |
| Turning Radius | 2235 mm |
| Length of track on ground | 2075 mm |
| Track Width | 450 mm |

⊖ Features

| | |
|-------------------------------------|-------------------------------------|
| Joystick Control | <input checked="" type="checkbox"/> |
| Air Conditioning | <input checked="" type="checkbox"/> |
| Backup Alarm | <input type="checkbox"/> |
| BICS System (Interlock) | <input type="checkbox"/> |
| Cab Heater | <input checked="" type="checkbox"/> |
| Operating Lights | <input type="checkbox"/> |
| Suspension Seat | <input type="checkbox"/> |
| Two Speed Travel | <input checked="" type="checkbox"/> |
| Deluxe Instrumentation | <input checked="" type="checkbox"/> |
| Engine Shutdown | <input type="checkbox"/> |
| Hydraulic Bucket Positioning | <input checked="" type="checkbox"/> |
| High Flow Option | <input checked="" type="checkbox"/> |
| Auxiliary Hydraulics | <input type="checkbox"/> |
| Bob-Tach Attachment System | <input type="checkbox"/> |
| Power Bob-Tach | <input checked="" type="checkbox"/> |
| ACS (Switchable Controls) | <input checked="" type="checkbox"/> |
| Ride Control | <input checked="" type="checkbox"/> |
| Horn | <input type="checkbox"/> |

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.