

Skid-Steer Loaders / S100 Skid-Steer Loader

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat S100

⊖ Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	26.5 kW
Turbocharged Engine	N/A

⊖ Performance

Rated Operating Capacity (SAE)	454 kg
Tipping Load	908 kg
Operating Weight	1,856 kg
Travel Speed	10.3 km/h

⊖ Capacities

Fuel Tank	45 l
------------------	------

⊖ Hydraulic System

System Relief @ Quick Couplers	206,84 bar
Auxiliary Std Flow	49.6 l/min
Auxiliary High Flow	n/a

⊖ Dimansion

Length	2,263 mm
Length without Attachment	2,263 mm
Length with Standard Bucket	2,800 mm
Width	1167 mm
Width (with bucket)	1270 mm
Height	1,877 mm
Height with Operator Cab	1,877 mm
Height to Bucket Hinge Pin	2632 mm
Reach @ Maximum Height	390 mm
Turning Radius	1,731 mm
Wheelbase	818 mm

⊖ Features

Joystick Control	N/A
Air Conditioning	N/A
Adjustable Seat	■
Backup Alarm	■
BICS System (Interlock)	■
Cab Enclosure	<input checked="" type="checkbox"/>
Sound Option	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	■
Parking Brake	■
Radio	N/A
Rear Window	■
Top Window	<input checked="" type="checkbox"/>
Lift-Arm Support	■
Seat Belt	■
Suspension Seat	<input checked="" type="checkbox"/>
Two Speed Travel	N/A
Deluxe Instrumentation	N/A
Engine Shutdown	N/A
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	N/A
Auxiliary Hydraulics	■
Spark Arrestor Muffler	■
Bob-Tach Attachment System	■
Power Bob-Tach	N/A
ACS (Switchable Controls)	N/A
Ride Control	N/A
Rear Hydraulics	N/A
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.